



## Enamelled wire

### Standard

ST RK 2280-2013

### Description

Enamelled wire of types ПЭЭИ (1,2)-200 and ПЭИИ (1,2)-210 is produced from Copper wire rod of diameter 8,0mm only upon customers request. The wire has a circular cross-section with a diameter ranging from 0,2mm to 2,0 mm.

### Usage

Used in the construction of electrical motors, appliances and equipment (transformers, speakers, electromagnets, generators etc.).

### Other

Packaging – Diameter 0,200 MM to 0,670 MM– packed in coils of types K200, K250;  
Diameter 0,700 MM to 2,000 MM – packed in coils of types A250/400 (with plastic cases).  
Transportation – by auto transport or by railway in containers.

ADVAITA TRADE DMCC

+971 4 421 9449  
WWW.ADVAITA.TRADE

UNIT NO. 3406-A,  
PLATINUM TOWER,  
PLOT NO: JLT-PH1-I2, CLUSTER I,  
JUMEIRAH LAKES TOWERS,  
DUBAI, UNITED ARAB EMIRATES,  
P.O. BOX 336137

COMPANY IS  
REGISTERED &  
LICENSED AS A  
FREEZONE COMPANY  
UNDER THE RULES & REGULATIONS  
OF  
DMCC